



## IC BUS®

### ICE 30 KW DC FAST CHARGER

A compact DCFC capable of charging with one or two connectors, this DC Wallbox is designed for easy wall mounting or can be attached to a pedestal. The 30 kW Charger is easy to operate with an intuitive touchscreen display and is ideal for fleet charging and a variety of parking applications where shorter charge times are necessary.



#### SPECIFICATIONS

**Max Power Output:** 30 kW

**Output Voltage Range:** 150 to 1000Vdc

**Cable Options:** CCS1 Connector - Option of 16ft or 25ft cables (recommended)

**Facility Power Requirements (Volts):** 480V 3 Phase

**Facility Power Requirements (Amps)\*:** 50

\* Per Charger



#### KEY BENEFITS & FEATURES

##### Estimated Charge Time

- 210 kWh Battery - 6 Hours\*\*
- 315 kWh Battery - 9 Hours\*\*

- User-friendly control interface allows for access management via PIN or RFID accessibility
- OCPP 1.6 standard supports interoperability cross back end platforms
- LTE Modem and LAN
- TUV certification to UL 2202 to ensure safety
- 480V 3-phase input for high-efficiency conversion
- DIN 70212 and ISO 15118-2 protocol supported
- Hot galvanized steel, plastic facade, and tempered glass screen construction ensures longevity

\*\*20% to 100% state of charge, room temperature current production CATL LFP Batteries



#### MOUNTING METHOD

Wall-mounted or pedestal



#### DIMENSIONS (D X W X H) & WEIGHT

34.6" x 25.25" x 74.8" / 155lbs